SAFE WORK METHOD STATEMENT (SWMS)

Business name

Document: SWMS-001 Rev 1
Prepared: 9 Nov 2026
Review by: 9 Dec 2026
Highest risk after controls: Medium

1. BUSINESS AND JOB DETAILS

Job	Wet area waterproofing	**Start date**	9 Nov 2026
Working hours	7:00 am to 3:30 pm	**Trade**	Tiling

2. HIGH RISK CONSTRUCTION WORK COVERED BY THIS SWMS

	Risk of a person falling more than 2 metres		Work on or near chemical, fuel or refrigerant lines
	Work on a telecommunication tower		Work on or near energised electrical installations or services
	Demolition of an element of a structure that is load-bearing or related to its physical integrity		Work in an area that may have a contaminated or flammable atmosphere
	Likely to involve disturbing asbestos		Work involving tilt-up or precast concrete elements
	Structural alterations or repairs that require temporary support to prevent collapse		Work on, in or next to a road, railway, shipping lane or other traffic corridor in use by traffic other than pedestrians
	Work in or near a confined space		Work in an area with movement of powered mobile plant
	Work in or near a shaft or trench with an excavated depth greater than 1.5 metres		Work in an area with artificial extremes of temperature
	Work in or near a tunnel		Work in or near water or other liquid that involves a risk of drowning
	Use of explosives		Diving work
	Work on or near pressurised gas distribution mains or piping		

3. JOB STEPS, HAZARDS AND CONTROLS

#	Job step	Hazards	Risk before	Controls	Risk after	Responsible
1	Check the substrate is sheeted, clean, dry and cured, and keep occupants out of the room	Working in an occupied home or building Slips and trips	**Medium Possible / Moderate**	1.1 Plan noisy, dusty or risky work for when the building is empty. [Eliminate] 1.2 Close off the work area with barriers, plastic sheeting or locked doors, and put up signs. [Isolate] 1.3 Keep fire exits and paths clear at all times. [Administrative] 1.4 Tell occupants before you turn off power, water or gas, and before noisy or dusty work. [Administrative] 1.5 Lock away tools, chemicals and materials each day, out of reach of children. [Administrative]	**Low Unlikely / Minor**	Site supervisor

#	Job step	Hazards	Risk before	Controls	Risk after	Responsible
				1.6 Clean up dust and debris at the end of each day. [Administrative] 1.7 Plan walkways and keep them clear of materials, hoses and leads. [Eliminate] 1.8 Run leads and hoses overhead on hooks or stands, or along walls, not across walkways. [Engineering] 1.9 Fill or cover holes, and lay boards or mats on muddy access paths. [Engineering] 1.10 Clean up offcuts, packaging and spills as you go, not at the end of the day. [Administrative] 1.11 Keep work areas, stairs and access paths well lit. [Administrative] 1.12 Wear safety boots with good grip, laced up. [PPE]		
2	Read the safety data sheets and set up fans or open windows, as solvent membranes give off fumes	Hazardous chemicals Rules: WHS Regulation 2011, Chapter 7 Hazardous chemicals	**Medium Possible / Moderate**	2.1 Choose the least harmful product that does the job, for example water-based instead of solvent-based. [Substitute] 2.2 Use chemicals in well-ventilated areas, or use fans and extraction in closed rooms. [Engineering] 2.3 Hazardous chemicals: see step 7 for the full controls [Administrative]	**Medium Unlikely / Moderate**	Site supervisor
3	Have a licensed electrician isolate or make safe power points and lights in the room if they will get wet, and run tools through RCD protection	Electric shock from leads and power tools Rules: WHS Regulation 2011, Part 4.7 and AS/NZS 3012	**High Possible / Major**	3.1 Use battery-powered tools where you can. [Substitute] 3.2 Plug all tools into an RCD-protected outlet or a portable RCD. [Engineering] 3.3 Keep leads off the ground and out of water, using lead stands or hooks. [Engineering] 3.4 Check leads, plugs and tools before every use. Tag out and remove anything damaged. [Administrative] 3.5 Test and tag leads, tools and RCDs at the intervals in AS/NZS 3012 (every 3 months on construction sites). Push-button test portable RCDs before each use. [Administrative] 3.6 Do not use tools in rain or wet areas unless they are rated for it. [Administrative] 3.7 Wear safety boots and dry gloves. [PPE]	**Low Rare / Major**	Site supervisor
4	Prepare the surface, grinding with extraction	Silica dust from concrete, brick, stone and tiles General dust Loud noise Rules: WHS Regulations, Chapter 8A (Crystalline silica substances and engineered stone); WHS Regulation 2011, Part 4.1 Noise	**Extreme Likely / Catastrophic**	4.1 If the job involves engineered stone: do not supply, fabricate or install engineered stone benchtops, panels or slabs (banned since 1 July 2024). Removing, repairing or making minor changes to existing engineered stone is only allowed with water suppression or on-tool extraction, a fitted respirator, and written notice to the regulator before the work starts. [Eliminate] 4.2 Order materials cut to size, or use low-dust methods such as score and snap or a block splitter. [Substitute] 4.3 Cut outdoors or in a separate area, with other people well away and upwind. [Isolate] 4.4 Use water on the blade or on-tool dust extraction connected to an H-class vacuum. [Engineering] 4.5 Clean up with a vacuum or wet methods. Never dry sweep or use compressed air. [Administrative] 4.6 If the cutting, grinding or drilling is high risk, prepare a silica risk control plan (or include the r.529CA assessment in this SWMS), train workers in	**Medium Unlikely / Moderate**	Site supervisor

#	Job step	Hazards	Risk before	Controls	Risk after	Responsible
				silica risks and give them the plan before work starts. [Administrative] 4.7 Wear a fit-tested P2 (or better) respirator. [PPE] 4.8 Use low-dust products, such as dust-reduced or pre-mixed compounds. [Substitute] 4.9 Seal off the work area with plastic sheeting in occupied buildings. [Isolate] 4.10 Use tools with dust extraction and a vacuum for clean up. [Engineering] 4.11 Lightly mist the area with water to keep dust down, away from anything electrical. [Engineering] 4.12 Never dry sweep or blow dust off with compressed air. [Administrative] 4.13 Use quieter tools and methods, such as cut-to-size materials, low-noise machines and battery tools. [Substitute] 4.14 Keep noisy plant away from work areas, and use screens or distance between the noise and people. [Isolate] 4.15 Keep tools maintained and use mufflers on compressors and generators. [Engineering] 4.16 Limit time on noisy tools and rotate workers. [Administrative] 4.17 If you have to shout to be heard 1 metre away, wear hearing protection. [Administrative] 4.18 Keep exposure below 85 dB(A) over 8 hours. Give hearing tests to workers who often need hearing protection. [Administrative]		
5	Fit bond breakers, puddle flanges and angles	Hazardous chemicals Cuts from sharp edges Rules: WHS Regulation 2011, Chapter 7 Hazardous chemicals	**Medium Possible / Moderate**	5.1 Read the Safety Data Sheet (SDS) before use and keep a register of hazardous chemicals on site. [Administrative] 5.2 Keep chemicals in labelled containers. Never decant into drink bottles. [Administrative] 5.3 Hazardous chemicals: see step 7 for the full controls [Administrative] 5.4 Deburr or cover sharp edges, and fit edge protectors on exposed sheet metal. [Engineering] 5.5 Use knives with retractable or self-retracting blades. [Engineering] 5.6 Cut away from your body and keep your other hand clear. [Administrative] 5.7 Put used blades in a blade bin or sharps container. [Administrative] 5.8 Use two people to handle large sheets of metal or glass. [Administrative] 5.9 Wear cut-resistant gloves and long sleeves. [PPE]	**Medium Unlikely / Moderate**	Site supervisor
6	Prime the surface, keeping all ignition sources away until it is dry	Flammable liquids and gases Hazardous chemicals Fire and emergencies Rules: WHS Regulation 2011, Chapter 7 Hazardous chemicals; WHS Regulation 2011, regulation 43 (emergency plans)	**High Unlikely / Catastrophic**	6.1 Use non-flammable or water-based products where you can. [Substitute] 6.2 Keep ignition sources away: no smoking, no hot work and no running engines near flammables. [Isolate] 6.3 Store fuels and solvents in approved, closed containers in a ventilated area away from the work. [Engineering] 6.4 Refuel equipment outdoors with the engine off and cool. [Administrative] 6.5 Keep only what you need for the day on site. [Administrative]	**Medium Unlikely / Moderate**	Site supervisor

#	Job step	Hazards	Risk before	Controls	Risk after	Responsible
				6.6 Store chemicals away from heat, food and drink, and keep products that react with each other apart. [Administrative] 6.7 Have eye wash and a spill kit nearby, and wash hands before eating. [Administrative] 6.8 Hazardous chemicals: see step 7 for the full controls [Administrative] 6.9 Provide fire extinguishers suited to the site, checked and easy to reach. [Engineering] 6.10 Keep exits and escape routes clear and signed. [Engineering] 6.11 Have a site emergency plan: alarm, exits, assembly point and emergency contacts. [Administrative] 6.12 Keep a stocked first aid kit and at least one trained first aider on site. [Administrative] 6.13 Know the site address and how emergency services get in. Call 000. [Administrative]		
7	Apply the membrane in coats with nitrile gloves and the respirator the SDS lists (an organic vapour cartridge for solvent or polyurethane products), kneeling on pads	Hazardous chemicals Repetitive work and awkward postures Rules: WHS Regulation 2011, Chapter 7 Hazardous chemicals; WHS Regulation 2011, Part 4.2 Hazardous manual tasks	**Medium Possible / Moderate**	7.1 Choose the least harmful product that does the job, for example water-based instead of solvent-based. [Substitute] 7.2 Use chemicals in well-ventilated areas, or use fans and extraction in closed rooms. [Engineering] 7.3 Read the Safety Data Sheet (SDS) before use and keep a register of hazardous chemicals on site. [Administrative] 7.4 Keep chemicals in labelled containers. Never decant into drink bottles. [Administrative] 7.5 Store chemicals away from heat, food and drink, and keep products that react with each other apart. [Administrative] 7.6 Have eye wash and a spill kit nearby, and wash hands before eating. [Administrative] 7.7 Wear chemical-resistant gloves and safety glasses or goggles as listed on the SDS. [PPE] 7.8 Use a respirator with the right cartridge if the SDS calls for one. [PPE] 7.9 Use tools that cut the effort: powered screwdrivers, long-handled tools and extension poles for overhead work. [Substitute] 7.10 Set work up at waist height on benches or trestles where you can. [Engineering] 7.11 Use light tools with good grips, and keep blades and bits sharp. [Engineering] 7.12 Rotate tasks and take short breaks every hour on repetitive work. [Administrative] 7.13 Warm up before heavy physical work and report aches and pains early. [Administrative] 7.14 Wear knee pads for kneeling work and gloves for grip. [PPE]	**Medium Unlikely / Moderate**	Site supervisor
8	Let it cure, then flood test	Slips and trips	**Medium Likely / Minor**	8.1 Slips and trips: see step 1 for the full controls [Administrative]	**Low Unlikely / Minor**	Site supervisor
9	Clean tools and dispose of waste membrane and tins properly	Hazardous chemicals Poor housekeeping and waste	**Medium Possible / Moderate**	9.1 Hazardous chemicals: see step 7 for the full controls [Administrative] 9.2 Order materials to size and send packaging back where you can. [Eliminate]	**Medium Unlikely / Moderate**	Site supervisor

#	Job step	Hazards	Risk before	Controls	Risk after	Responsible
		Rules: WHS Regulation 2011, Chapter 7 Hazardous chemicals		9.3 Put skip bins and waste chutes close to the work. [Engineering] 9.4 Clean as you go, and do a full clean up at the end of each day. [Administrative] 9.5 Keep exits, stairs and walkways clear at all times. [Administrative] 9.6 Stack materials neatly on level ground, away from edges. [Administrative] 9.7 Wear gloves when handling waste. [PPE]		

Risk key: risk = likelihood x consequence on a 5 x 5 matrix. Low, Medium, High, Extreme. Work must not start while the risk after controls is high or above. Controls are listed in order of the hierarchy of control: Eliminate, Substitute, Isolate, Engineering, Administrative, PPE.

4. PPE AND PERMITS

Required PPE	Permits and plans
Chemical-resistant gloves (nitrile) Safety glasses Half-face respirator (P2 or P3 filters) Knee pads P2 dust mask Steel cap boots Safety goggles Overalls Work gloves Hearing protection (earmuffs or plugs) Cut-resistant gloves	None required

5. PLANT AND EQUIPMENT

Plant / equipment	Licence or training needed	Inspection needed	Rego / ID	Last inspected	Certificate / report
Hand tools					
Angle grinder		Test and tag every 3 months on construction sites (AS/NZS 3012); visual check and RCD push-button test before use			
H-class vacuum		Test and tag every 3 months on construction sites (AS/NZS 3012); visual check and RCD push-button test before use			

6. TRAINING REQUIRED FOR THIS WORK

- Silica risk training before work starts (WHS Regulations r.529CD)

7. CREW COMPETENCY, TICKETS AND LICENCES

Crew listed at sign-on below, with ticket and licence numbers.

8. EMERGENCY ARRANGEMENTS

Emergency number	000	**First aid kit**	In the work vehicle
Fire extinguisher	In the work vehicle	**Alarm and evacuation**	Shout for help and stop work. Make the area safe and go to the assembly point. Call the emergency number and send someone to meet the ambulance.
Reporting incidents	Notify the regulator immediately of any notifiable incident and preserve the site.		

9. IMPLEMENTING, MONITORING AND REVIEWING THE CONTROLS

How they are put in place	Controls are set up before the work starts. The person responsible explains this SWMS to every worker before they start, and workers sign to confirm they understand it.	**How they are monitored**	The person responsible checks the controls are in place before work starts each day and during the work, and talks to the workers about any problems. Stop work and review this SWMS if the work changes, the controls are not working, after any incident, or if a worker raises a concern.
When it is reviewed	Reviewed when the work or site changes, after any incident, if a control is not working, or if a worker or health and safety representative asks.		

Legal basis: Work Health and Safety Regulations 2011, Part 6.3 (Victoria: OHS Regulations 2017). A SWMS must be prepared before any high risk construction work starts. It must list the high risk work, the hazards and risks, the control measures, and how those controls will be put in place, monitored and reviewed. It must be easy for the workers to read and understand.

Keep this SWMS, and every revised version, until the high risk construction work is finished, where workers and inspectors can see it on site. If a notifiable incident happens during the work, keep it for at least 2 years after the incident.

10. REVIEW AND AMENDMENT RECORD

Rev	Date	By	What changed
1	9 Nov 2026		First issue

11. SIGN-OFF

	Name	Signature	Date	
Prepared by				
Person responsible (supervisor)				
Principal contractor review				Accepted for use: Yes / No

By signing below, each worker confirms they were consulted on and have read and understood this SWMS, and will follow it. If the work cannot be done as this SWMS says, stop as soon as it is safe and do not restart until the SWMS is reviewed.

Name	Role / company	Tickets / licences	Inducted	Signature	Date

Name	Role / company	Tickets / licences	Inducted	Signature	Date